

NLS3 L-3/G-2

SUPERIOR PRODUCTIVITY IN NORMAL LOADING APPLICATIONS

- Classical non-directional pattern with wide tread**
 Benefit: Excellent traction in both directions; Excellent comfort, stability and flotation.
- Heavy casing design and blocks reinforced by a centerpiece tread belt**
 Benefit: Increased strength and load capacity.
- Special compounds and structure engineered to limit tread movement**
 Benefit: Low heat generation.



Size	Ply Rating	TRA Code	Rim	Dimension		Load Capacity		Inflation Pressure		Tread Depth (mm)	Type
				Section width (mm)	Overall diameter (mm)	10km/h	50km/h	10km/h	50km/h		
17.5-25	12	L-3/G-2	14.00/1.5	445	1350	6150	3650	350	225	26	TT/TL
17.5-25	16	L-3/G-2	14.00/1.5	445	1350	7300	4250	475	300	26	TT/TL
17.5-25	20	L-3/G-2	14.00/1.5	445	1350	8250	5000	575	400	26	TT/TL
20.5-25	16	L-3/G-2	17.00/2.0	520	1490	8250	5450	350	275	28	TT/TL
20.5-25	20	L-3/G-2	17.00/2.0	520	1490	9500	6000	450	325	28	TT/TL
23.5-25	16	L-3/G-2	19.50/2.5	595	1615	9500	6150	300	225	33.5	TT/TL
23.5-25	20	L-3/G-2	19.50/2.5	595	1615	10900	7300	375	300	33.5	TT/TL
23.5-25	24	L-3/G-2	19.50/2.5	595	1615	12500	8000	475	350	33.5	TT/TL
26.5-25	20	L-3/G-2	22.00/3.0	675	1750	13200	8250	350	250	39	TT/TL
26.5-25	24	L-3/G-2	22.00/3.0	675	1750	14000	9250	400	300	39	TT/TL
26.5-25	28	L-3/G-2	22.00/3.0	675	1750	15500	10000	475	350	39	TT/TL
14/90-16	14	G-2	16 x 10/8	295	920	1560	/	280	/	16	TT